

ATF Multi Vehicle

Description and Properties:

ATF Multi Vehicle fluid is an Automatic Transmission Fluid which is made by multi-vehicle anti-shudder additive technology optimized for passenger car applications.

ATF Multi Vehicle affords following benefits:

- Exceptional oxidation behavior
- Anti-shudder durability
- smoother shifts over a long period of time
- excellent anti-rust properties
- low foaming tendency

Specification / Recommendations:

GM DEXRON II / II-D / II-E / III-G / III-H

Allison C-4, TES-295, TES-389

BMW/Mini P/N 81 22 9 400 272/275

BMW/Mini P/N 81 22 9 407 858/859

BMW/Mini P/N 83 22 0 024 249/359

BMW/Mini P/N 83 22 0 026 922 (BMW 7045 E)

BMW/Mini P/N 83 22 0 402 413

BMW/Mini P/N 83 22 0 403 248/249

BMW/Mini P/N 83 22 7 542 290

BMW/Mini P/N 83 22 9 407 765 (BMW LA 2634)

Chrysler/Dodge/Jeep ATF+2/ATF+3/ATF+4

Chrysler/Dodge/Jeep AS68RC ATF

Chrysler/Dodge/Jeep SP-III

Daimler/Mercedes MB 236.3, 236.5, 236.6, 236.7

MB 236.8, 236.9, 236.10, 236.91

FORD WSS-M2C919-E (Mercon V)

FORD/Lincoln/Mercury P/N XT-2-QDX [M]

FORD/Lincoln/Mercury P/N XT-2-QSM [Syn]

FORD/Lincoln/Mercury P/N XT-5-QM or -DM [V]

FORD/Lincoln/Mercury P/N XT-8-QAW [Premium]

FORD/Lincoln/Mercury P/N XT-9-QMM5 [FNR5]

FORD/Lincoln/Mercury WSS-M2C922-A1

GM/GMC/Opel/Saturn P/N 19 40 700/767

VW/Audi G 052 025 A2, G 052 055

VW/Audi G 052 162 (A1, A2)

VW/Audi G 052 990 (A2), G 055 025 (A2)

GM/GMC/Opel/Saturn P/N 21005966 (transaxle)

GM/GMC/Opel/Saturn P/N 22717466

GM/GMC/Opel/Saturn P/N 88900925/9986195

GM/GMC/Opel/Saturn T-IV, Type A Suffix A

Jaguar JLM 20238 / 20292 / 21044 / K17

Jaguar WSS-M2C922-A1

Aisin Warner JWS 3309

Land Rover Texaco ETL-7045E

MAN 339 A

Mercon V

Mobil ATF 3309

Porsche P/N 000 043 204 41

Porsche P/N 000 043 205 09

Porsche P/N 999 917 547 00 (A2)

PSA Peugeot Citroen P/N Z 000169756

Renault Matic D2

Renk Genuine Oil

Saab 3309 - T-IV

Shell 3403-M115, LA 2634

Texaco ETL 7045E / 8072B, N402

Voith H55.6335.XX

Voith Svc Bltn # 013 / 118

Volvo P/N 1161521

Volvo P/N 1161540 / 1161640

Volvo P/N 1273,41

ZF TE-ML 11A / 11B



Typical Values:

ATF Multi Vehicle	Unit	Value	Method
Density at 15°C	kg/m ³	850	DIN 51 757
Color		rot	Visuell
Viscosity at 40°C	mm ² /s	38,2	DIN 51 562
Viskosität bei 100°C	mm ² /s	7,0	DIN 51 562
Viscosity index		150	DIN ISO 2909
Pourpoint	°C	-45	DIN ISO 3016
Flashpoint	°C	228	DIN ISO 2592

*Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.
Further information available by MSDS.*

Hengst SE

Nienkamp 55-85

48147 Münster

Germany

Tel.: +49 251 20202-0