

15W-40 A3/B4 Pro

Description and Properties:

15W-40 A3/B4 Pro is a multigrade motor oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality base oils and additives of most progressive technology. Suitable also under severe operating conditions in modern passenger car engines, turbo- or non-turbo charged.

15W-40 A3/B4 Pro by its optimized formulation provides lowered fuel- and oil consumption. Because of its extended viscosity range the all seasons use is possible. The dispersing power, expressed by the performance level of this product, prevents deposits and pluggings in the oil circuit and thus keeps the engine clean. Modern oxidation inhibitors extend the service life of the oil and the optimal wear protection cares for long engine life.

Specification / Recommendations:

ACEA A3- / B4-12
API SL / CF

VW 505 00
MB 229.1

Typical Values:

15W-40 A3/B4 Pro	Unit	Value	Method
Density at 15°C	kg/m ³	873	DIN 51 757
Viscosity at 40°C	mm ² /s	115	DIN 51 562
Viscosity at 100°C	mm ² /s	15,3	DIN 51 562
Viscosity Index		140	DIN ISO 2909
CCS at -20°C	mPa.s	5380	DIN 51 377
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	230	DIN ISO 2592
TBN	mg KOH/g	10,1	DIN ISO 3771

*Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.
Further information available by MSDS.*

Hengst SE

Nienkamp 55-85
48147 Münster
Germany
Tel.: +49 251 20202-0

