

5W-30 C3 Pro

Description and Properties:

5W-30 C3 Pro is a high performance fuel economy oil made from synthetic base oils. It is foreseen for the all-seasons use in passenger cars most modern gasoline- and diesel-engines, even with unit-injector. Due to its progressive conception it provides an extremely wide range of performances:

- Low sulphur-, phosphorus- and ash-content reduce poisoning of catalysators in gasoline engines and decrease the built-up of particles in the diesel particulate filter (DPF) and assist thus the environmental protection by lower pollution.
- Novel high performance additivation assures optimal wear protection and best motor cleanliness.
- Excellent thermal oxidation stability reduces oil aging and allows longer drain intervals at maximum motor protection.
- Best low temperature properties enable unproblematic cold-start of the motor and contribute decisively to a longer operating life of the engine by rapid oil circulation.

Specification / Recommendations:

ACEA C3	Renault RN 0700 / 0710
API SN / CF	BMW Longlife-04
VW 502 00 / 505 00 / 505 01	MB 229.51 (deckt 229.31 ab)
GM dexos 2	MB 229.52
MB 226.5	

Typical Values:

5W-30 C3 Pro	Unit	Value	Method
Density at 15°C	kg/m ³	853	DIN 51 757
Viscosity at 40°C	mm ² /s	65,8	DIN 51 562
Viscosity at 100°C	mm ² /s	11,4	DIN 51 562
Viscosity Index		165	DIN ISO 2909
CCS at -30°C	mPa.s	5080	DIN 51 377
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	230	DIN ISO 2592

*Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.
Further information available by MSDS.*

Hengst SE

Nienkamp 55-85
48147 Münster
Germany
Tel.: +49 251 20202-0

