

# 20W-50 A3/B4 Pro

## Description and Properties:

**20W-50 A3/B4 Pro** is a high performance crankcase oil to be used in passenger cars and light duty vehicles. It can be recommended for the consumption-optimised modern gasoline engine as well as for the high-output turbo charged diesel engine.

**20W-50 A3/B4 Pro** is a motor oil, blended from synthetic and mineral base oils and most modern additives. The excellent wear protection and the very good detergency/dispersancy, which efficiently control sludge build-up, have to be highlighted. Because of the multigrade properties based on the viscosity range 20W50 the oil especially is recommended for all-season use in warm and in tropical climates.

## Specification / Recommendations:

ACEA A3- / B4-12  
API SL / CF  
MB 229.1

## Typical Values:

20W-50 A3/B4 Pro	Unit	Value	Method
Density at 15°C	kg/m <sup>3</sup>	885	DIN 51 757
Viscosity at 40°C	mm <sup>2</sup> /s	157	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	18,4	DIN 51 562
Viscosity Index		132	DIN ISO 2909
CCS at -15°C	mPa.s	5960	DIN 51 377
Pourpoint	°C	-36	DIN ISO 3016
Flashpoint	°C	238	DIN ISO 2592
TBN	mg KOH/g	10,1	DIN ISO 3771

*Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.  
Further information available by MSDS.*

## Hengst SE

Nienkamp 55-85  
48147 Münster  
Germany  
Tel.: +49 251 20202-0

