



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
X0030S-1	0W-30 LONGLIFE III	Fully Synthetic Engine Oil	1	12/624
X0030S-4	0W-30 LONGLIFE III	Fully Synthetic Engine Oil	4	4/192
X0030S-20	0W-30 LONGLIFE III	Fully Synthetic Engine Oil	20	1/45
X0030S-205	0W-30 LONGLIFE III	Fully Synthetic Engine Oil	205	1/4
X0030S-1K	0W-30 LONGLIFE III	Fully Synthetic Engine Oil	1000	1/1



0W-30 LONGLIFE III

FULLY SYNTHETIC ENGINE OIL

This is a full synthetic lubricant based on carefully selected very high quality base oils. It is specifically formulated to meet the most demanding VW specifications available today-VW 504.00 and 507.00-as well as the Long Life III requirements of the VAG Group. It is a Mid SAPS oil which meets Euro 4 and Euro 5 norms and provides protection to the Diesel Particulate Filter.

Applications

Backwards compatible: 504.00 and 507.00 supersedes all previous VW specifications (502.00, 503.00, 503.01, 505.00, 506.00 and 506.01).All vehicles in the VAG Group (Volkswagen, Audi, Seat, Skoda) with extended oil drain intervals (30.000 km or 2 years) from 2007 onwards. Note: For V10 TDI and 5-cylinder 2.5 TDI engines, prior to 2007, where the 506.01 specification has to be used, this oil is not recommended. The first generation engines with pump injector units should use the 505.01 specification. Meets all engine protection requirements of ACEA C2*.

Features

After treatment protection: full after treatment system protection. Total engine protection: outstanding engine cleanliness and durability. Fuel economy: lower fuel consumption and CO2 emissions.

Specification Levels

ACEA C2*	PORSCHE C30
ACEA C3	VW 504.00/507.00
FIAT 9.55535-DS1	VW TL 52 545
FIAT 9.55535-GS1	

Typical Characteristics

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.842
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	59.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.7
Viscosity index	ASTM D2270	-	197
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	8.3
Pour point	ASTM D6892	°C	-48