



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
X1060S-1	10W-60 PRO S	Fully Synthetic Engine Oil	1	12/624
X1060S-4	10W-60 PRO S	Fully Synthetic Engine Oil	4	4/192
X1060S-20	10W-60 PRO S	Fully Synthetic Engine Oil	20	1/45
X1060S-205	10W-60 PRO S	Fully Synthetic Engine Oil	205	1/4
X1060S-1K	10W-60 PRO S	Fully Synthetic Engine Oil	1000	1/1



10W-60 PRO S

FULLY SYNTHETIC ENGINE OIL

This is a full synthetic lubricant based on carefully selected very high quality base oils of the latest generation for the lubrication of all gasoline and diesel engines with turbo.

Applications

4 stroke gasoline engines, multi-valves, turbo.4 stroke diesel engines, with or without turbo.

Features

cold start: very good fluidity at low temperature. Total engine protection: outstanding engine cleanliness and durability.

Specification Levels

ACEA A3/B4-08	MB 229.3
API SN/CF	VW 501 01
BMW LONGLIFE-01	VW 505 00
BMW M-MODELS	

Typical Characteristics

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.855
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	156
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	25
Viscosity index	ASTM D2270	-	194
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	9.5
Pour point	ASTM D6892	°C	-36
Sulfated Ash	ASTM D874	Mass %	1.0
Flash Point COC	ASTM D92	°C	235