



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
X2050S01-1	20W-50	Multigrade Engine Oil	1	12/624
X2050S01-4	20W-50	Multigrade Engine Oil	4	4/192
X2050S01-20	20W-50	Multigrade Engine Oil	20	1/45
X2050S01-205	20W-50	Multigrade Engine Oil	205	1/4
X2050S01-1K	20W-50	Multigrade Engine Oil	1000	1/1



# 20W-50

## MULTIGRADE ENGINE OIL

A high-performance engine oil formulated with highly refined base oil and advanced additive technology to provide enhanced engine performance and excellent protection in all passenger cars and light-duty truck engines.

### Applications

Hengst API SJ/CF 20W-50 can be used in most North American and Asian model gasoline engine vehicles

### Features

Enhanced engine protection against engine wear and deposit under severe operating conditions. Strong thermal and oxidation stability resulting in highly stable oil viscosity. Excellent engine cleanliness and longer engine service life. Good compatibility with engine parts (gasket and seal)

### Specification Levels

API SF/CD

MB 226.3

MIL-L-46152B

### Typical Characteristics

Test	Method	Unit	Average Results
Appearance	Visual		C&B
Density at 30°C	ASTM D4052	g/ml	0.8810
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	167
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	18.2
Viscosity index	ASTM D2270		121
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7
Water & Sediments	ASTM D445	%	5650