



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
X0530S03-1	5W-30 C3 PRO	Fully Synthetic Engine Oil	1	12/624
X0530S03-4	5W-30 C3 PRO	Fully Synthetic Engine Oil	4	4/192
X0530S03-20	5W-30 C3 PRO	Fully Synthetic Engine Oil	20	1/45
X0530S03-205	5W-30 C3 PRO	Fully Synthetic Engine Oil	205	1/4
X0530S03-1K	5W-30 C3 PRO	Fully Synthetic Engine Oil	1000	1/1



5W-30 C3 PRO

FULLY SYNTHETIC ENGINE OIL

A full synthetic lubricant which delivers a cleaner and better performance engine without compromising the change interval. Suitable for a wide ranging models and brands.

Applications

Suitable for applications with and without after exhaust treatment where ACEA C2/C3 oil is needed. Able to meet Renault RN 17 specification which covers also RN0700 & RN0710 specifications.

Features

Formulated to last, thus reducing change interval and stock level.

Specification Levels

ACEA: C2-16	FIAT: 9.55535-S3	MB: 229.52
ACEA: C3-16	GM: DEXOS2™	RENAULT: RN17 LEVEL
API: SN	IVECO: 18-1811 CLASSE SC1	VW: 505.00
BMW: LONGLIFE-04	MB: 229.31	VW: 505.01
FIAT: 9.55535-S1	MB: 229.51	

Typical Characteristics

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	70.9
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	12.0
Viscosity index	ASTM D2270	-	167
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	7.8
Pour point	ASTM D6892	°C	-45
Sulfated Ash	ASTM D874	Mass %	0.78