



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
X0530S05-1	5W-30 LONGLIFE III PLUS	Fully Synthetic Engine Oil	1	12/624
X0530S05-4	5W-30 LONGLIFE III PLUS	Fully Synthetic Engine Oil	4	4/192
X0530S05-20	5W-30 LONGLIFE III PLUS	Fully Synthetic Engine Oil	20	1/45
X0530S05-205	5W-30 LONGLIFE III PLUS	Fully Synthetic Engine Oil	205	1/4
X0530S05-1K	5W-30 LONGLIFE III PLUS	Fully Synthetic Engine Oil	1000	1/1



5W-30 LONGLIFE III PLUS

FULLY SYNTHETIC ENGINE OIL

This is a full synthetic lubricant based on carefully selected very high quality base oils. It is specifically formulated to meet the most demanding VW specifications available today-VW 504.00 and 507.00-as well as the Long Life III requirements of the VAG Group. It is a Mid SAPS oil which meets Euro 4, Euro 5 and Euro 6 norms and provides protection to the Diesel Particulate Filter.

Applications

Backwards compatible: 504.00 and 507.00 supersedes all previous VW specifications. Suitable for all VAG Group cars with extended change intervals (30.000 km or 2 years). Specifically for downsized Turbocharged Gasoline Direct Injection (TGDI) engines to mitigate LSPI (Low Speed Pre Ignition).

Features

After treatment protection: full after treatment system protection. Total engine protection: outstanding engine cleanliness and durability. Fuel economy: lower fuel consumption and CO2 emissions.

Specification Levels

ACEA C2*	MB 229.31	PORSCHE C30
ACEA C3	MB 229.51	VW 503.01
API SP	MB 229.52	VW 504.00/507.00
BMW LONGLIFE-04	OPEL OV0401547	

Typical Characteristics

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	64.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.6
Viscosity index	ASTM D2270	-	177
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8.4
Pour point	ASTM D6892	°C	-42
Sulfated Ash	ASTM D874	Mass %	0.78
Flash Point COC	ASTM D92	°C	230
CCS viscosity at -30°C	ASTM D5293	mPa.s	5600