



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
X0530S04-1	5W-30 PRO	Fully Synthetic Engine Oil	1	12/624
X0530S04-4	5W-30 PRO	Fully Synthetic Engine Oil	4	4/192
X0530S04-20	5W-30 PRO	Fully Synthetic Engine Oil	20	1/45
X0530S04-205	5W-30 PRO	Fully Synthetic Engine Oil	205	1/4
X0530S04-1K	5W-30 PRO	Fully Synthetic Engine Oil	1000	1/1



5W-30 PRO

FULLY SYNTHETIC ENGINE OIL

Superior low viscosity and fluidity ensures that this full synthetic lubricant achieve low level of CO₂ emission and low fuel consumption. Formulated with additives to minimize soot level and maintain a clean engine.

Applications

This motor oil has been specially designed to meet the latest ILSAC GF-6A standard for stringent fuel economy and CO₂ emission. Meet the latest requirements for American and Asian passenger cars.

Features

Total engine protection: outstanding engine cleanliness and durability. Cold start: excellent fluidity at low temperature. Fuel economy: lower fuel consumption and CO₂ emissions.

Specification Levels

API: SN PLUS	CHRYSLER: MS 13340	FORD: WSS-M2C946-A	ILSAC: GF-5
API: SN/RC	CHRYSLER: MS 6395	FORD: WSS-M2C947-A	ILSAC: GF-6 A
API: SP	FIAT: 9.55535-CR1	FORD: WSS-M2C961-A	
API: SP/RC	FORD: WSS-M2C945-A	GM: DEXOS1™ GEN 2	

Typical Characteristics

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.848
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	60.7
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	10.8
Viscosity index	ASTM D2270	-	172
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	8.5
Pour point	ASTM D6892	°C	-36 same
Flash Point COC	ASTM D92	°C	225