



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
X0540S02-1	5W-40 C3 PLUS	Fully Synthetic Engine Oil	1	12/624
X0540S02-4	5W-40 C3 PLUS	Fully Synthetic Engine Oil	4	4/192
X0540S02-20	5W-40 C3 PLUS	Fully Synthetic Engine Oil	20	1/45
X0540S02-205	5W-40 C3 PLUS	Fully Synthetic Engine Oil	205	1/4
X0540S02-1K	5W-40 C3 PLUS	Fully Synthetic Engine Oil	1000	1/1



5W-40 C3 PLUS

FULLY SYNTHETIC ENGINE OIL

Full synthetic engine oil formulated to meet the high performing petrol engines requirement. With highly durable formulation, this lubricant ensure great fuel economy and total engine protection. Suitable for hybrid cars when the OEM specifications.

Applications

Performance enhancer for several W12, V10 and V8 engines of multiple manufacturers. Highest quality properties endorsed by the VW 511 00 and Porsche C40 specifications. Top quality widens the coverage including Audi, Bentley and Lamborghini cars.

Features

After treatment protection: full after treatment system protection. Total engine protection: outstanding engine cleanliness and durability. Fuel economy: superior fuel economy and CO2 reduction.

Specification Levels

ACEA C3-16	MB 226.5	RENAULT RN 0700
API SN/CF	MB 229.51	RENAULT RN 0710
BMW LONGLIFE-04	MB 229.52	VW 511.00
GM DEXOS2™	PORSCHE C40	

Typical Characteristics

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.850
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	73.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.5
Viscosity index	ASTM D2270	-	191
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7.8
Pour point	ASTM D6892	°C	-42
Sulfated Ash	ASTM D874	Mass %	0.79
Flash Point COC	ASTM D92	°C	222