



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
X0550S-1	5W-50 PRO	Fully Synthetic Engine Oil	1	12/624
X0550S-4	5W-50 PRO	Fully Synthetic Engine Oil	4	4/192
X0550S-20	5W-50 PRO	Fully Synthetic Engine Oil	20	1/45
X0550S-205	5W-50 PRO	Fully Synthetic Engine Oil	205	1/4
X0550S-1K	5W-50 PRO	Fully Synthetic Engine Oil	1000	1/1



5W-50 PRO

FULLY SYNTHETIC ENGINE OIL

This is a full synthetic lubricant based on carefully selected very high quality base oils with a high viscosity index for the lubrication of gasoline and diesel engines with turbocharging. This oil is distinguished by an excellent fluidity at low temperature, which allows a perfect cold start, along with a high viscosity at hot engine.

Applications

This oil is used in 4-stroke gasoline engines, multi valves, and 4-stroke diesel engines with or without turbo. It is specifically suitable for sporty driving conditions.

Features

Total engine protection: performance in keeping the engine clean. cold start: excellent fluidity at low temperature. Driving style: sporty driving.

Specification Levels

ACEA A3/B4-08	MB 229.3
API SN/CF	VW 501 01
BMW LONGLIFE-01	VW 505 00

Typical Characteristics

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	118
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	18
Viscosity index	ASTM D2270	-	170
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	9.6
Pour point	ASTM D6892	°C	-30
Sulfated Ash	ASTM D874	Mass %	1.1
Flash Point COC	ASTM D92	°C	235
CCS viscosity at -25°C	ASTM D5293	mPa.s	6200