



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
X75140S-1	75W-140 GL-5 LS	Synthetic Transmission Oil	1	12/624
X75140S-4	75W-140 GL-5 LS	Synthetic Transmission Oil	4	4/192
X75140S-20	75W-140 GL-5 LS	Synthetic Transmission Oil	20	1/45
X75140S-205	75W-140 GL-5 LS	Synthetic Transmission Oil	205	1/4
X75140S-1K	75W-140 GL-5 LS	Synthetic Transmission Oil	1000	1/1



75W-140 GL-5 LS

SYNTHETIC TRANSMISSION OIL

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This is a high performance transmission oil for all differentials, including those equipped with a “limited slip” mechanism. It is characterized by an exceptionally high viscosity stability at different temperatures and a very high fluidity at low temperature.

Applications

This product is used in highly loaded axles and reduction gears of cars, trucks and off-road equipment. It has “limited-slip” characteristics, and is specifically recommended for 4X4 vehicles.

Features

Frictional properties: very smooth gear shifting, no vibration. Anti-wear protection: extended transmission life. Extended oil life: excellent thermal and oxidation stability.

Specification Levels

API GL-5

BMW MSP/A

FORD WSS-M2C187-A

FORD WSS-M2C192-A

FORD WSS-M2C192-A+/M2C118-A

GM 12346140

GM 1942386 MIL-L-2105 C

MIL-L-2105 D

Typical Characteristics

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.905
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	170
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	26.5
Viscosity index	ASTM D2270		195
Pour point	ASTM D6892	°C	-51
Flash Point COC	ASTM D92	°C	190