



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
XATF3S02-1	ATF 3 LONGLIFE	Synthetic Automatic Transmission Fluid	1	12/624
XATF3S02-4	ATF 3 LONGLIFE	Synthetic Automatic Transmission Fluid	4	4/192
XATF3S02-20	ATF 3 LONGLIFE	Synthetic Automatic Transmission Fluid	20	1/45
XATF3S02-205	ATF 3 LONGLIFE	Synthetic Automatic Transmission Fluid	205	1/4
XATF3S02-1K	ATF 3 LONGLIFE	Synthetic Automatic Transmission Fluid	1000	1/1



ATF 3 Longlife

SYNTHETIC AUTOMATIC TRANSMISSION FLUID

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This is an oil with a very high viscosity index for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.

Applications

This oil is used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements.

Features

Frictional properties: smooth shift performance. Anti-wear protection: extended transmission life. Extended oil life: excellent thermal and oxidation stability.

Specification Levels

ALLISON C4	MB 236.9
FORD MERCON	VOITH H55.6335XX
GM 6417-M DEXRON III-G	VOLVO STD 1273,40 (97340)
MAN 339 V1/Z1	VOLVO STD 1273,41 (97341)
MB 236.5	ZF TE-ML 03D/04D/09

Typical Characteristics

Test	Method	Unit	Average Results
Colour	ASTM D1500		Amber
Density at 15°C	ASTM D4052	g/ml	0.855
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	33.9
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	7.1
Viscosity index	ASTM D2270		179
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	17500
Flash Point COC	ASTM D92	°C	196