



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
XATF689S-1	ATF 689 PRO	Fully Synthetic Automatic Transmission Fluid	1	12/624
XATF689S-4	ATF 689 PRO	Fully Synthetic Automatic Transmission Fluid	4	4/192
XATF689S-20	ATF 689 PRO	Fully Synthetic Automatic Transmission Fluid	20	1/45
XATF689S-205	ATF 689 PRO	Fully Synthetic Automatic Transmission Fluid	205	1/4
XATF689S-1K	ATF 689 PRO	Fully Synthetic Automatic Transmission Fluid	1000	1/1



ATF 689 PRO

FULLY SYNTHETIC AUTOMATIC TRANSMISSION FLUID

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6, 8 and 9-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

Applications

Exclusively intended for the ZF 6,8 and 9 speed automatic transmissions, as fitted in VW, BMW, Jaguar, Land Rover, Jeep, Chrysler and FIAT group.

Features

Anti-wear protection: significantly extended transmission life. Frictional properties: very smooth gear shifting, no vibration. Extended oil life: excellent thermal and oxidation stability.

Specification Levels

BMW 83222152426	JAGUAR 02JDE26444
CHRYSLER 68157995AA	LAND ROVER LR023288
FIAT 9.55550-AV5	VW G060162

Typical Characteristics

Test	Method	Unit	Average Results
Colour	ASTM D1500		Green
Density at 15°C	ASTM D4052	g/ml	0.845
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	28.1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	5.94
Viscosity index	ASTM D2270		164
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	9500
Flash Point COC	ASTM D92	°C	210