



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
XATF6HPS-1	ATF 6HP	Fully Synthetic Automatic Transmission Fluid	1	12/624
XATF6HPS-4	ATF 6HP	Fully Synthetic Automatic Transmission Fluid	4	4/192
XATF6HPS-20	ATF 6HP	Fully Synthetic Automatic Transmission Fluid	20	1/45
XATF6HPS-205	ATF 6HP	Fully Synthetic Automatic Transmission Fluid	205	1/4
XATF6HPS-1K	ATF 6HP	Fully Synthetic Automatic Transmission Fluid	1000	1/1



ATF 6HP

FULLY SYNTHETIC AUTOMATIC TRANSMISSION FLUID

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

Applications

Mainly intended for the ZF-6 speed automatic transmissions, as fitted in BMW, Jaguar and Land Rover, it is also suitable for other OEMs, who recommend this type of fluid (e.g. Audi Quattro).

Features

Anti-wear protection: significantly extended transmission life. Frictional properties: very smooth gear shifting, no vibration. Extended oil life: excellent thermal and oxidation stability.

Specification Levels

AML 4G4319A509/AA/S	JAGUAR FLUID 8432
BENTLEY PY112995PA	LAND ROVER TYK500050
BMW 83220142516	MASERATI 231603
BMW M-1375.4	VW G 055 005
HYUNDAI 040000C90SG	ZF TE-ML 11

Typical Characteristics

Test	Method	Unit	Average Results
Colour	ASTM D1500		Amber
Density at 15°C	ASTM D4052	g/ml	0.845
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	31
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	6.2
Viscosity index	ASTM D2270		153
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	9500
Flash Point COC	ASTM D92	°C	202