



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
XATF2S-1	ATF DEXRON 2	Automatic Transmission Fluid	1	12/624
XATF2S-4	ATF DEXRON 2	Automatic Transmission Fluid	4	4/192
XATF2S-20	ATF DEXRON 2	Automatic Transmission Fluid	20	1/45
XATF2S-205	ATF DEXRON 2	Automatic Transmission Fluid	205	1/4
XATF2S-1K	ATF DEXRON 2	Automatic Transmission Fluid	1000	1/1



# ATF Dexron 2

## AUTOMATIC TRANSMISSION FLUID

This is an oil with a high viscosity index for automatic transmissions. It is characterized by a high chemical stability, increased anti-wear properties and an excellent resistance against ageing.

### Applications

It can be used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron II-D requirements.

### Features

Anti-wear protection: extended transmission life. Extended oil life: optimized thermal and oxidation stability.

### Specification Levels

ALLISON C4	MB 236.5
CATERPILLAR TO-2	MB 236.7
FORD M2C-138CJ, MERCON	VOITH H55.6335XX
GM 6137-M DEXRON II-D	ZF-TE ML 03D/04D/09
MAN 339 V1/Z1	ZF-TE ML 11A/14A/17C

### Typical Characteristics

Test	Method	Unit	Average Results
Colour	ASTM D1500		Red
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	37
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	7.4
Viscosity index	ASTM D2270		170
Pour point	ASTM D6892	°C	-39
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	45000
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	3