



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
XATF7501-1	ATF MB 7-SPEED	Fully Synthetic Automatic Transmission Fluid	1	12/624
XATF7501-4	ATF MB 7-SPEED	Fully Synthetic Automatic Transmission Fluid	4	4/192
XATF7501-20	ATF MB 7-SPEED	Fully Synthetic Automatic Transmission Fluid	20	1/45
XATF7501-205	ATF MB 7-SPEED	Fully Synthetic Automatic Transmission Fluid	205	1/4
XATF7501-1K	ATF MB 7-SPEED	Fully Synthetic Automatic Transmission Fluid	1000	1/1



# ATF MB 7-Speed

## FULLY SYNTHETIC AUTOMATIC TRANSMISSION FLUID

This is a full synthetic lubricant based on carefully selected very high quality base oils, mainly intended for all MB 7-speed automatic transmissions and NAG-V Sport transmissions. It provides excellent frictional durability and superior performance.

### Applications

This ATF is recommended for the 7G-Tronic and 5-Speed automatic transmissions of Mercedes-Benz. Due to its specific composition and characteristics, it is not suitable for other applications.

### Features

Anti-wear protection: significantly extended transmission life. Frictional properties: very smooth gear shifting, no vibration. Extended oil life: excellent thermal and oxidation stability.

### Specification Levels

MB 236.14

### Typical Characteristics

Test	Method	Unit	Average Results
Colour	Visual		Red
Density at 15°C	ASTM D4052	g/ml	0.848
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	28.6
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	5.9
Viscosity index	ASTM D2270		154
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	11800
Flash Point COC	ASTM D92	°C	206