



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
XATF7S-1	ATF MB 7 FE	Fully Synthetic Automatic Transmission Fluid	1	12/624
XATF7S-4	ATF MB 7 FE	Fully Synthetic Automatic Transmission Fluid	4	4/192
XATF7S-20	ATF MB 7 FE	Fully Synthetic Automatic Transmission Fluid	20	1/45
XATF7S-205	ATF MB 7 FE	Fully Synthetic Automatic Transmission Fluid	205	1/4
XATF7S-1K	ATF MB 7 FE	Fully Synthetic Automatic Transmission Fluid	1000	1/1



ATF MB 7 FE

FULLY SYNTHETIC AUTOMATIC TRANSMISSION FLUID

This is a full synthetic lubricant based on carefully selected very high quality base oils, intended for the latest MB 7-speed automatic transmissions from MB (NAG2FE+). It provides excellent frictional durability, superior performance and fuel economy.

Applications

This product is recommended for sports vehicles (NAG2FE+) and is not backwards compatible with the previous 5- and 7- speed transmissions , which require MB 236.10, 236.12, 236.14.

Features

Anti-wear protection: significantly extended transmission life. Frictional properties: very smooth gear shifting, no vibration. Extended oil life: excellent thermal and oxidation stability.

Specification Levels

MB 236.15

Typical Characteristics

Test	Method	Unit	Average Results
Colour	Visual		Dark Blue
Density at 15°C	ASTM D4052	g/ml	0.842
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	17.3
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	4.4
Viscosity index	ASTM D2270		172
Pour point	ASTM D6892	°C	-54
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	3500
Flash Point COC	ASTM D92	°C	178