



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
XATF9S-1	ATF MB 9-SPEED	Fully Synthetic Automatic Transmission Fluid	1	12/624
XATF9S-4	ATF MB 9-SPEED	Fully Synthetic Automatic Transmission Fluid	4	4/192
XATF9S-20	ATF MB 9-SPEED	Fully Synthetic Automatic Transmission Fluid	20	1/45
XATF9S-205	ATF MB 9-SPEED	Fully Synthetic Automatic Transmission Fluid	205	1/4
XATF9S-1K	ATF MB 9-SPEED	Fully Synthetic Automatic Transmission Fluid	1000	1/1



ATF MB 9-SPEED

FULLY SYNTHETIC AUTOMATIC TRANSMISSION FLUID

This is a synthetic automatic transmission fluid with a special selection of top quality base oils and a specific additive package to ensure the smooth functioning of automatic transmissions of Mercedes-Benz. It is an ATF of the newest generation developed for 9-gear automatic transmissions of Mercedes-Benz vehicles. It guarantees an excellent wear protection in every operating situation.

Applications

This ATF is developed for use in the newest 9G-Tronic automatic transmission of the Series W9A 700 by Mercedes-Benz, also known as NAG3 (New Automatic Transmission of the 3rd Generation). It should be used in MB automatic transmissions requiring the specification MB 236.17. It is backward compatible with the former MB 236.16.

Features

Excellent shear stability, high thermal and oxidative stability, superb protection against wear.

Specification Levels

MB 236.17

Typical Characteristics

Test	Method	Unit	Average Results
Color	ASTM D1500		Yellow
Density at 15°C	ASTM D4052	g/ml	0.843
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	4,8
Viscosity index	ASTM D2270		166
Pour point	ASTM D6892	°C	-54