



Hengst Type	Description 1	Description 2	Packing Litre	Packing Unit
XPSFS-1	PSF MB	Power Steering Fluid	1	12/624



# PSF MB

## POWER STEERING FLUID

This is a full synthetic lubricant based on carefully selected very highly refined base oils for power steering , meeting the requirements of most American, Japanese and European manufacturers.

### Applications

PSF MB's versatile nature guarantees it can be used in power steering, automatic transmissions and torque convertors for most passenger cars, off-road vehicles and SUVs.

### Features

Frictional properties: very smooth operation, no vibration. Anti-wear protection: significantly extended transmission life. Extended oil life: excellent thermal and oxidation stability.

### Specification Levels

MB236.3

### Typical Characteristics

Test	Method	Unit	Average Results
Color	Visual		Amber
Density at 15°C	ASTM D4052	g/ml	0.849
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	32.7
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	7.02
Viscosity index	ASTM D2270		184
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	12000
Flash Point COC	ASTM D92	°C	218