

5W-30 A3/B4 Pro

Description:

5W-30 A3/B4 Pro is a high-performance low-friction oil, which is designed for all gasoline and diesel engines of passenger cars, and which especially can be used for fuel injected and turbo charged engines. It is blended from high quality synthetic base oils and selected additives. This results in a lubricant quality which fulfills and exceeds all requirements of modern passenger car engines.

Properties:

5W-30 A3/B4 Pro has following advantages to be pointed out

- excellent cold start and fast oil feed even at temperatures down to lower than -30°C assure fuel- and oil-economy.
- optimized high temperature viscosity to meet latest requirements leads to low oil-caused emissions.
- high wear and corrosion protection and a very good dispersibility ensure an excellent cleanliness of the engine and guarantee a long motor life.
- all-season use thanks to outstanding temperature-viscosity properties and reliable performance reserves, even with long drain intervals.

Specification / Recommendations:

ACEA A3 / B4	VW 502 00 / 505 00
API SL	MB 229.3
BMW LL 98	PSA B71 2296
Renault RN 0710 / 0700	Fiat 9.55535-M2
Porsche A40	Opel GM-LL-B-025

Typical values:

5W-30 A3/B4 Pro	Unit	Value	Method
Density at 15°C	kg/m ³	853	DIN 51 757
Viscosity at 100°C		12,0	DIN 51 562
Viscosity Index	mPa.s	170	DIN ISO 2909
CCS at -30°C	°C	5590	DIN 51 377
Pourpoint	mPa.s	-42	DIN ISO 3016
Flashpoint	°C	228	DIN ISO 2592
TBN	mg KOH/g	11,0	DIN ISO 3771

Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded. Further information is available on the safety data sheet.

Hengst SE

Nienkamp 55-85
48147 Münster · Germany
Tel.: +49 251 20202-0

