

5W-30 A5/B5 Pro

Description:

5W-30 A5/B5 Pro is a high-alloyed all-seasons oil for those passenger car engines, which require fuel economy (FE) oils. Low viscosity of special base oils coming from the synthesis-technology provides by fast oil circulation and low frictional resistance noticeable reduction of fuel consumption and pollutant emission.

Properties:

5W-30 A5/B5 Pro is equal to all thermal and mechanical loads, which may occur in modern fuel economy passenger car engines.

- high cleaning-and dit holding capacity (Detergent/Dispersant) provide excellent motor cleanliness.
- outstanding fuel economy properties by special friction reducing additives.
- cost-effective all-seasons oil with noticeable fuel reduction.
- takes care for the environment by reduced emissions of CO2 and particles.

Specification / Recommendations:

ACEA A5 / B5 API SL Renault RN 0700 Jaguar / Land Rover STJLR.03.5003 FORD WSS-M2C 913-B / C / D

Typical Values:

5W-30 A5/B5 Pro	Unit	Value	Method
Density at 15°C	kg/m ³	848	DIN 51 757
Viscosity at 100°C		9,9	DIN 51 562
Viscosity Index	mPa.s	176	DIN ISO 2909
CCS at -30°C	°C	3410	DIN 51 377
Pourpoint	mPa.s	-42	DIN ISO 3016
Flashpoint	°C	230	DIN ISO 2592
TBN	mg KOH/g	9,5	DIN ISO 3771

Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded. Further information available by MSDS.

Hengst SE Nienkamp 55-85 48147 Münster Germany Tel.: +49 251 20202-0



Made in Germany