

0W-30 A3/B4 Pro

Description and Properties:

0W-30 A3/B4 Pro is a high-alloyed all-seasons oil for those passenger car engines, which require fuel economy (FE) oils. Low viscosity of special base oils coming from the synthesis-technology provides by fast oil circulation and low frictional resistance noticeable reduction of fuel consumption and pollutant emission.

0W-30 A3/B4 Pro is equal to all thermal and mechanical loads, which may occur in modern fuel economy passenger car engines.

- high cleaning-and dit holding capacity (Detergent/Dispersant) provide excellent motor cleanliness.
- outstanding fuel economy properties by special friction reducing additives.
- cost-effective all-seasons oil with noticeable fuel reduction.
- takes care for the environment by reduced emissions of CO2 and particles.

Specification / Recommendations:

ACEA A3/B4 VW 502 00 / VW 505 00 API SL Renault RN0700 / RN0710 MB 229.5 / MB 229.3 Volvo VCC95200356

Typical Values:

0W-30 A3/B4 Pro	Unit	Value	Method
Density at 15°C	kg/m³	845	DIN 51 757
Viscosity at 40°C	mm²/s	58,9	DIN 51 562
Viscosity at 100°C	mm²/s	10,5	DIN 51 562
Viscosity Index		169	DIN ISO 2909
CCS at -35°C	mPa.s	5750	DIN 51 377
Pourpoint	°C	-45	DIN ISO 3016
Flashpoint	°C	230	DIN ISO 2592
TBN	mg KOH/g	10,1	DIN ISO 3771

Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded. Further information available by MSDS.

Hengst SE

Nienkamp 55-85 48147 Münster Germany

Germany

Tel.: +49 251 20202-0



