

STANLEY DUST MASK SYFFP2 TECHNICAL DATASHEET

PRODUCT DETAILS

Material: 40GSM non-woven PP + 60GSM Melt Blown Filter+ 100GSM PP

Color: white

Classification: FFP2 NR

FEATURES AND BENEFITS

- Single-use filtering face-piece respirator.
- Adjustable alu nose clip to fit face better
- High-density nose pad foam to protect from leaking
- ABS Exhalation valve to help breath easily
- 280% Elongation spandex straps, breaking load>20KN
- Filters at least 96% of particles
- Valid: 5 years

APPLICATIONS

These respirators maybe suitable for the following suggested applications (but are not limited to):

- Textile industry
- Wood-working
- Underground Civil Engineering
- Welding work

CERTIFICATION

This product has been tested according to the following European Standard:

- EN149: 2001 +A1: 2009. Respiratory protective devices. Filtering half masks to protect against particles. Requirements, testing, marking. It complies with European Regulation (EU) 2016/425 on Personal Protective Equipment (PPE). Category III.
- EU type examination certificate (module B) issued by BSI, notified body CE2797. The PPE is subject to the conformity to Type based on Quality Assurance of the Production Process (Module D) set out in Annex VII under surveillance of BSI Netherlands, notified body CE2797.

TRANSPORTATION & STORAGE CONDITION

- Maximum relative humidity of Transportation & storage condition <70%
- Temperature range of Transportation & storage: -20 to 40 degrees.

