

STANLEY EU FFP3 DISPOSABLE RESPIRATOR SYFFP3

TECHNICAL DATASHEET

PRODUCT DETAILS

Material: 60gsm non-woven PP + 60gsm cotton+ 100gsm Melt blown filter+ 100gsm PP

Color: white **Weight:** 24g

Classification: FFP3 NR D



FEATURES AND BENEFITS

- 99%+ filter effective Single-use filtering respirator.
- Adjustable plastic coating alu nose clip
- ABS Exhalation valve to help breath easily.
- 280% Elongation straps, breaking load>20KN
- High-density full inner seal foam to protect from leaking.
- Adjustable 7 elastane yarns spandex straps, comfortable & anti-allergy
- Dolomite clogging test.
- Valid: 5 years

APPLICATIONS

These respirators maybe suitable for the following suggested applications (but are not limited to):

- Sanding of hard wood (beech oak)
- Impact stripping of paint
- Treatment of wood using copper chrome or arsenic based products
- Sanding of cements

ADVANTAGES

- The mask is in compliance with dolomite dust clogging test.
- The ergonomic shell-shape mask grants a remarkable adherence to the face and a comfort. suitable to daily use.
- The shape of the half mask with an increased size reduces the breathing resistance thanks to a wider filtering surface and improves comfort considerably.

CERTIFICATION

This product has been tested according to the following European Standard:

- EN149: 2001 +A1: 2009. Respiratory protective devices. Filtering half masks to protect against particles. Requirements, testing, marking. It complies with European Regulation (EU) 2016/425 on Personal Protective Equipment (PPE). Category III. EU type examination. Certificate (module B) issued by BSI, notified body n°2797.

TRANSPORTATION & STORAGE CONDITION

- Maximum relative humidity of Transportation & storage condition <70%
- Temperature range of Transportation & storage: -20 to 40 degrees.