

10W-40 E7 HD Pro

Description and Properties:

10W-40 E7 HD Pro is produced from mineral base oils and hydro-cracked products. Combined with a special additive package it has become a quality product, which satisfies the requirements of the modern engine generation of diesel motors and gasoline motors as well. Especially it is applicable for engines, which because of the advanced construction, as turbocharger or poor-mix operation, make very special demands on the lubricant.

10W-40 E7 HD Pro gives following advantages:

- trouble-free operation even under extreme operating conditions
- oxidation stability, which reduces early oil aging even at high temperatures
- outstanding wear protection, which assures a long engine-life
- allows maximal oil drain intervals, like specified by the manufacturer

Specification / Recommendations:

ACEA E7-16	Mack EO-M Plus & EO-N
API CI-4 / CF / SL	MAN M 3275
Caterpillar ECF-1a & ECF-2	MB 228.3
Cummins CES 20077 / 20078	MTU Type 2
DDC 93K215	Renault RLD / RLD2
Global DHD-1	VOLVO VDS-3
Jaso DH-1	DEUTZ DQC III-10

Typical Values:

10W-40 E7 HD Pro	Unit	Value	Method
Density at 15°C	kg/m ³	864	DIN 51 757
Viscosity at 40°C	mm ² /s	99,6	DIN 51 562
Viscosity at 100°C	mm ² /s	14,6	DIN 51 562
Viscosity Index		152	DIN ISO 2909
CCS at -25°C	mPa.s	6110	DIN 51 377
Pourpoint	°C	-39	DIN ISO 3016
Flashpoint	°C	234	DIN ISO 2592
TBN	mg KOH/g	10,8	DIN ISO 3771

*Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.
Further information available by MSDS.*

Hengst SE

Nienkamp 55-85
48147 Münster
Germany
Tel.: +49 251 20202-0