

ATF 7 Speed ECO

Description:

ATF 7 Speed ECO is a high performance ATF for use in the latest Mercedes-Benz 7-speed automatic transmission (NAG2FE+) from 21.06.2010. It is based on fundamental oils from the synthesis technology and superior performance package. An extremely shear stable VI improver in connection with modern anti-wear additives and friction modifiers guarantee stable lasting excellent smooth switching behavior, outstanding oxidation stability and a superior coefficient of friction stability. The lowered viscosity ensures maximum fuel economy.

Application:

ATF 7 Speed ECO is intended for use in the latest 7-speed automatic transmission from Mercedes-Benz. It is **not** backward compatible, so **not** suitable for use in older transmissions. Note manufacturer's instructions!

Specification / Recommendations:

MB 236.15

Typical Values:

ATF 7 Speed ECO	Unit	Value	Method
Density at 15°C	kg/m ³	845	DIN 51 757
Appearance		Blau	
Viscosity at 40°C	mm ² /s	23,0	DIN 51 562
Viscosity at 100°C	mm ² /s	5,0	DIN 51 562
Viscosity index		160	DIN ISO 2909
Flash point COC	°C	> 190	DIN ISO 2592
Pourpoint	°C	-45	DIN ISO 3016

*Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.
Further information available by MSDS.*

Hengst SE

Nienkamp 55-85
48147 Münster
Germany
Tel.: +49 251 20202-0

