

ATF Dex II D

Description and Properties:

ATF Dex II D is a highly developed gear oil, which meets the requirements of the most modern automatic gears of passenger and commercial cars, other vehicles and aggregates.

ATF Dex II D meets the strongest requirements of gear- and machine manufacturers and due to its high quality level it provides optimal operating reliability and endurance of all aggregates to be lubricated

- excellent lubrication of highly stressed torque converters and load change gears
- very good low- and high-temperature properties
- optimal balanced frictional behavior for short gear change intervals
- very good shear stability, low foaming tendency and long operating expectations

Application:

ATF Dex II D is an Automatic Transmission Fluid to be universally used in all automatic transmissions, power steering and hydraulics, the manufacturer of which have recommended an ATF according GM-specification DEXRON® II

Specification / Recommendations:

GM DEXRON® II D

Allison C3/C4

MAN 339, Typ D

MB 236.7

ZF TE-ML 03D, 04D, 09A, 11A, 14A

Voith

Ford SQM-9010B ; Ford M2C-138CJ, 166H, 185A

Caterpillar TO-2

Typical Values:

ATF Dex II D	Unit	Value	Method
Density at 15	kg/m ³	851	DIN 51 757
Viscosity at 40°C	mm ² /s	37,00	DIN 51 562
Viscosity at 100°C	mm ² /s	7,937	DIN 51 562
Viscosity Index		195	DIN ISO 2909
Pourpoint	°C	-45	DIN ISO 3016
Flash Point	°C	218	DIN ISO 2592

Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.

Further information available by MSDS.

Hengst SE

Nienkamp 55-85

48147 Münster

Germany

Tel.: +49 251 20202-0

