

ATF Dex VI

Description:

ATF Dex VI fluid is an low viscosity Automatic Transmission Fluid which is made with a special additive technology, optimized for a wide range of passenger car applications.

Application:

ATF Dex VI is used in an extensive range of European, American and Asian passenger car service fill applications. Additional it can be used in commercial vehicle applications and power steering, too.

Properties:

ATF Dex VI affords following benefits:

- Exceptional oxidation behavior
- Low viscosity for high fuel economy
- smoother shifts over a long period of time
- excellent anti-rust properties
- low foaming tendency

Specification / Recommendations:

DEXRON VI

Aisin Warner AW-1

Aisin Warner JWS 3324

Bentley P/N PY112995PA

BMW/Mini P/N 83 22 0 142 516

BMW/Mini P/N 83 22 0 397 114

BMW/Mini P/N 83 22 2 163 514 (BMW 8072 B)

Chrysler/Dodge/Jeep P/N 05127382AA

Chrysler/Dodge/Jeep P/N 68043742AA

Daimler / Mercedes MB 236.12, 236.14, 236.41

FORD/Lincoln/Mercury P/N XT-10-QLV [LV]

FORD/Lincoln/Mercury P/N XT-6-QSP or -DSP [SP]

GM/GMC/Opel/Saturn AW1

GM/GMC/Opel/Saturn P/N 88863400, 88863401

Honda/Acura DW-1

Honda 082000-9017 (ATF Type 3.1)

Hyundai/Kia NWS-9638 T-5

Hyundai/Kia P/N 040000C90SG

Hyundai/Kia SP-IV / SPH-IV

Jaguar Fluid 8432

JASO M315, Class 1A

Land Rover P/N TYK500050, LR0022460

Maserati P/N 231603

Mazda FW 6A EL, FW 6AX EL

Mazda FZ

Mercon LV

Mitsubishi ATF-J3

Mitsubishi SP-IV

Nissan/Infinity Matic-S

Porsche P/N 000 043 304 00

Saab P/N 93 165 147 - AW-1

Shell 3353, Shell 134, Shell 1375.4

Toyota/Lexus/Scion WS

VW/Audi G 052 533, G 055 005 (-A, A2)

VW/Audi G 055 540 (A2)



Typical Values:

ATF Dex VI	Unit	Value	Method
Density at 15	kg/m ³	844	DIN 51 757
Colour		red	Visuell
Viscosity at 40°C	mm ² /s	26,4	DIN 51 562
Viscosity at 100°C	mm ² /s	5,6	DIN 51 562
Viscosity Index		160	DIN ISO 2909
Pourpoint	°C	-45	DIN ISO 3016
Flash Point	°C	226	DIN ISO 2592

*Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.
Further information available by MSDS.*

Hengst SE

Nienkamp 55-85

48147 Münster

Germany

Tel.: +49 251 20202-0